



Loctite® brand Fixmaster® Flooring Products are specialty repair materials that fill or level industrial surfaces. A cost-effective, high-performance alternative to conventional flooring systems, these epoxies are non-shrinking and have good chemical and corrosion resistance, and high compression strength.

FLOORING & GROUT

Loctite® Fixmaster® Deep Pour Grout

Aggregate-filled, epoxy system for pours up to 6" deep, including self-leveling applications under rails and sole plates. High strength material bonds to steel, concrete, and itself. Withstands high torque loading.

Loctite® Fixmaster® Super Grout

Fixmaster® Super Grout aggregate-filled epoxy system is designed for grouting up to 18" deep, including self-leveling applications under rails and sole plates under typical dry service temperatures of -29°C to +107°C (-20°F to +225°F). Loctite® Fixmaster® Super Grout is a 100% solids epoxy system that is non-shrinking, chemical and corrosion resistant, stronger than concrete, and withstands high torque loading.

Loctite® Fixmaster® Fast Set Grout

Self-leveling, non-shrinking grout for installing machinery, setting anchor bolts. Cures quickly. Can be poured up to 1" thick. Compression strength and chemical resistance are superior to concrete. Forms strong bonds to old concrete and to itself.

Loctite® Fixmaster® High Performance Quartz

Trowelable epoxy for repairing and protecting floors exposed to concentrated acids, alkalis, and solvents. Recommended for restoring and protecting old concrete.

Loctite® Fixmaster® Floor Fill

Trowelable. For repairing and resurfacing cracks in concrete floors. Bonds to old and new concrete and provides greater strength and chemical resistance.

Loctite® Fixmaster® Magna-Crete™

A two-component, rapid setting concrete repair and grouting system. Chemically resistant to most common liquids and chemicals. Bonds to concrete, wood, glass, steel, and other construction materials.

Loctite® Fixmaster® Marine Chocking

Self-leveling, fast curing, non-shrinking grout. Outstanding chemical and vibration resistance and compressive strength to withstand maximum loads.

LOCTITE® BRAND FIXMASTER®
FLOORING & GROUT PROPERTIES CHART

PRODUCT	Item Number	Container	Coverage	Color	Mixed Viscosity, cP	Maximum Temperature, °F	Compressive Strength, psi	Working Time, Minutes	Functional Cure, Hours	Mix Ratio by Volume, r : h	Mix Ratio by Weight, r : h	Agency Approvals
Fixmaster® Deep Pour Grout	99545	5 gal. kit	660 in. ³	Black	Pourable	225	14,500	30	24	-	-	CFIA
Fixmaster® Fast Set Grout	39637	2 gal. kit	347 in. ³	Red	5,500	200	14,500	10	12	100:11.7	100:6.5	CFIA
Fixmaster® Floor Fill	99361 99365	10 lb. kit 40 lb. kit	133 in. ³ 532 in. ³	Grey	Semi-Pourable	225	15,000	40	24	-	-	CFIA
Fixmaster® High Performance Quartz	96495	42 lb. kit	15 ft. ² *	Grey	Paste	150	12,000	45 Primer 60 Topcoat	24	-	-	CFIA
Fixmaster® Magna-Crete®	95551 95555	1 gal. kit 5 gal. kit	4.8 ft. ² * 21.6 ft. ² *	Grey	-	2000	13,000	15	1-2	-	-	CFIA
Fixmaster® Magna-Crete™ Activator	36334	10 lb. bottle	-	-	-	-	-	-	-	-	-	-
Fixmaster® Marine Chocking	97572 96102 37316**	2 gal. kit 2 gal. kit 1 gal. kit	370 in. ³ 370 in. ³ 185 in. ³	Green Orange Orange	15,000	250	22,000	10	24	100:11.6	100:6.9	ABS, CFIA
Fixmaster® Super Grout	33510	5 gal. kit	620 in. ³	Red	Pourable	225	12,900	285	24	-	-	-

* Coverage at 1/4" thickness.

**Made-to-order item. May require up to four week lead time.

LOCTITE® BRAND
FIXMASTER® FLOORING &
GROUT APPLICATION
SELECTION GUIDE

PRODUCT	Anchor Bolt Fastening	Chocking (Ships)	Concrete Floor Repair	Engine Installation	Grout Heavy Equipment 1" to 6"	Grout Heavy Equipment to 18"	Grout Light Equipment 1" or Less	Leveling Equipment	Acid/Chemical Resistant Floor Repair	Ramps, Loading Docks	Highways, Roadways	Leveling Floors
Fixmaster® Deep Pour Grout				●	●		●	●				
Fixmaster® Fast Set Grout	●			●	●		●	●				
Fixmaster® Floor Fill			●	●					●			
Fixmaster® High Performance Quartz			●						●			
Fixmaster® Magna-Crete™			●		●		●			●	●	●
Fixmaster® Marine Chocking		●		●			●	●				
Fixmaster® Super Grout				●	●	●	●					

● Preferred choice ● Good choice

